

Proportional Relief Valves, High Pressure

**Part No.**

SS-4R3A5-EP

Part Description

Stainless Steel High Pressure Proportional Relief Valve, 1/4 in. MNPT x 1/4 in. FNPT, Ethylene Propylene Seal

Specifications

General	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/4 in.
Connection 1 Type	Male NPT
Connection 2 Size	1/4 in.
Connection 2 Type	Female NPT
eClass (4.1)	37010901
eClass (5.1.4)	37019901
eClass (6.0)	37010901
eClass (6.1)	37019901
Lubricant	Dow Corning Molykote 55 Grease
Max Temperature Pressure Rating	250°F @ 4910 PSIG /121°C @ 338 BAR
Room Temperature Pressure Rating	6000 PSIG @ 100°F /413 BAR @ 37°C
Seal Material	Ethylene Propylene
Service Class	High Pressure
Size	1/8 in.
Testing	No Optional Testing
UNSPSC (10.0)	40141606
UNSPSC (11.0501)	40141606
UNSPSC (13.0601)	40141606
UNSPSC (15.1)	40141606
UNSPSC (17.1001)	40141600
UNSPSC (4.03)	40141606
UNSPSC (PGE)	401416AL
UNSPSC (SWG01)	40141606
Valve Material	316 Stainless Steel

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

 Caution: Do not mix or interchange valve components with those of other manufacturers.

2018 Copyright Swagelok Company