

Lift Check Valves

**Part No.**

SS-58F8

Part Description

Stainless Steel Lift Check Valve, 2.20 Cv, 1/2 in. FNPT

Specifications

General	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/2 in.
Connection 2 Type	Female NPT
eClass (4.1)	37010801
eClass (5.1.4)	27300400
eClass (6.0)	27292001
eClass (6.1)	27292001
Lubricant	Nickel Never Seez
Max Temperature Pressure Rating	400°F @ 4280 PSIG /204°C @ 294 BAR
Room Temperature Pressure Rating	4600 PSIG @ 100°F /316 BAR @ 37°C
Surface Finish	Standard
Testing	No Optional Testing
UNSPSC (10.0)	40141634
UNSPSC (11.0501)	40141634
UNSPSC (13.0601)	40141634
UNSPSC (15.1)	40141659
UNSPSC (17.1001)	40141600
UNSPSC (4.03)	40141601
UNSPSC (PGE)	401416AL
UNSPSC (SWG01)	40141601
Valve Material	316 Stainless Steel

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

⚠ Caution: Do not mix or interchange valve components with those of other manufacturers.

